S00022864
SUPERFUND RECORDS

Site: Chico Ya Ganty

ID#: KUD18014/842

Break: 44

Other: Out#15

4.4.88

SURFACE MINE WASTE AT THE GALENA SUBSITE

CHEROKEE COUNTY, KANSAS

April 4, 1988

Gary Andes
P. O. Box 893
Cannon Beach, OR 97110

Introduction

Under the authority of CERCLA and SARA, the U.S. Environmental Protection Agency has been studying an area known as the Cherokee County Superfund site in southeast Kansas, an area of former lead-zinc mining. The site has been subdivided by EPA into six subsites with the largest being the Galena Subsite which surrounds the City of Galena, Kansas and encompasses about 18 square miles (Figure 1 from OUFS).

An Operable Unit Feasibility Study (OUFS) for the groundwater and surface water has recently been prepared by EPA. This OUFS develops and evaluates several potential remedial alternatives to decrease the risks to public health and the environment posed by past (1876-1960's) mining activities and the mining-related contaminants in surface mine waster, disturbed subsurface mineralized zones, and in the shallow groundwater and surface water systems within the Galena Subsite.

Inherent in most of the remedial action alternatives evaluated by EPA is either treatment or removal and containment of the surface mine wastes. According to EPA's public health risk assessment in the OUFS, risks are present to both children and adults from ingestion of groundwater and mine wastes. In addition, EPA believes that all potential exposure pathways have a common source in the mine wastes.

After a development, screening, and evaluation process EPA has proposed an alternative which would remove and treat the surface mine wastes, thereby hopefully reducing the surface sources of metal contaminants and the subsurface formation of acid mine drainage. Surface mine wastes would be removed by excavation and then treated by milling and flotation processes to concentrate the lead and zinc sulfides (for partial cost recovery). Tailing from the treatment process would be disposed of in the mine voids. Following surface mine waste removal, the disturbed land areas would be recontoured and vegetated.

A large factor to be considered in the evaluation of the alternatives is the quantity of surface mine waste to be removed and treated as this value has a significant bearing on the costs and time involved in the remedial action.

This study was commissioned to evaluate the existing surface mine waste data and provide an additional estimate of the quantity and types of surface mine wastes in the Galena Subsite. Field work was conducted from March 27 through April 1, 1988 at the Galena Subsite with literature review and calculations occurring before and after the field work.

Surface Mine Waste Types

As defined by EPA, mine wastes is a collective term that includes bullrock, dump material, chat, slag, and tailing all derived from mining and smelter activities. In this study bullrock and dump material were combined into one category as waste rock. In addition, two additional waste types were identified and categorized, overburden and stream sediments.


Bullrock is very coarse material and boulders removed in shaft excavation. Dump material is subeconomic ore from minus 1/4 inch to boulder size excavated from the subsurface workings and deposited on the surface in the process of mining. It is commonly mixed with the bullrock. Overburden is similar to dump material in that it is derived from removing the surface rocks over a shallow orebody and usually deposited next to the mine opening. All three of the above categories are usually mixed on the surface. Chat is a fine grained material, mostly chips of host rock, that has been milled to remove the sulfides. It is easily distinguished from the other waste materials by its smaller grain size and gray color. Stream sediments are materials found in the area streambeds from the erosional process on any of the above materials and may consist of a mixture of the other waste types, although usually smaller sized in nature.

Procedures

In addition to the maps and detailed data presented in the OUFS, black and white aerial photos taken in 1978 were obtained from the Soil Conservation Service. These photos were used in the field to outline and characterize the surface mine waste areas in the eight zones established by EPA for their analysis (Figure 2 from the OUFS) according to the five waste types previously described.

Areal extent of each waste type was estimated by actually walking each zone and outlining areas on the aerial photos in the field. Visible known locations and reference points such as streets or roads, ponds, buildings, powerlines, and streams were used to locate positions in the surface waste fields. Pacing of areas and piles was utilized as much as possible.

For individual piles an estimate of height was made by either assuming a total height in the case of a cone shaped pile or an average height in the case of an irregular shaped pile. Circumference of each pile was measured by pacing the surface contour of the pile base. Note was taken as to the location of any numbered and flagged survey stakes placed by EPA in their sampling program and height, width, length or circumference estimated for any piles so marked.



Larger areas of mine waste were walked and an estimate of average waste depth over the area made. Where minimal piles existed in an area or the area had some natural surface showing, the depth was usually estimated at three inches. Areas with larger piles or minimal natural surface were estimated at six inches depth. A shovel was utilized to did shallow holes to determine natural surface levels. addition, ravines and washouts, as well as mine shafts and pits, were utilized to ascertain the natural surface levels. Slope of the natural topography was also taken into account when estimating pile or area waste depths. Areas with larger heaped piles and/or spreadout zones were usually estimated at one foot in depth. Some areas mapped contained essentially one pile whose dimensions were estimated as described in the previous paragraph. Depth estimates also attempted to include the surface and mine shaft depressions which contained considerable mine waste in the slumped or cone shapes.

Areas on the marked up aerial photographs were determined by planimeter by Allgeier, Martin & Associates of Joplin, Missouri to obtain acreage figures for each mine waste area identified in the photographs.

Volumes for each area or pile were calculated using standard geometric formulas for cones, wedges, cubes, or cylinders from the dimensions estimated or measured in the field. Total zone volumes were then calculated by summing the previously calculated volumes of each waste type and subzone.

Interpretation of Results

Appendix A contains the marked up aerial photographs utilized to determine the areal extent of the various types of mine wastes. Appendix B contains the results of the planimetering of the areas. Table 1 presents a summary of the acreage of surface mine wastes by zone. Approximately 710 acres of surface mine wastes were identified in the eight zones delineated by EPA. A 1983 study by McCauley of mine and mill waste and disturbed areas in the Galena area yielded an estimate of 891 acres. This figure has been used by EPA directly in its cost estimate for reclamation. A comparison of McCauley's areas shown in Figure 3 and EPA's areas shown in Figure 4 with the Appendix A aerial photographs shows a general agreement regarding delineation of surface mine waste areas. The difference in estimated acreages probably is a function of the definition of waste coverage and the fact that some of McCauley's areas are outside the eight zones established by EPA. In particular, in Section 27 of Figure 3, some of the area shown as disturbed is actually natural ground surface. In addition, it is likely that some of the surface mine waste has been removed (chat for roadways and fill, for example) or disturbed areas reclaimed for other uses (such as areas 29 and 20 on Figure 3). In any case the


Table 1
Areas of Mine Waste


Area	Acres	Percent of Total
Zone l	109.94	15.5
Zone 2	97.96	13.8
Zone 3	95.03	13.4
Zone 4	29.25	4.1
Zone 5	145.98	20.6
Zone 6	47.48	6.7
Zone 7	133.34	18.8
Zone 8	50.80	7.2

Total 709.78 acres

3,435,335 yd²

30,918,017 ft²





LEGEND

AREAS OF SURFACE WASTES

Figure 4

Areas of Surface Wastes (from EPA OUFS Figure 6-2)

FIGURE 6-2
ALTERNATIVE 2

-8REMOVE AND TREAT SURFACE WASTES,
BACKFILL SHAFTS AND VOIDS
CHEROKEE CO KANSAS
GALENA SUBSITE—OUFS
GROUNDWATER/SURFACE WATER

710 acre estimate is most likely on the low side and it is probable that at least that amount would require reclamation if EPA's remedial alternative were implemented.

Appendix C contains the volumetric calculations for each waste area delineated on the aerial photographs. Table 2 presents a summary of the estimated volumes of surface mine waste by zone. Approximately 1,279,000 cubic yards of surface mine waste were estimated to exist within the eight zones delineated by EPA. This is nearly 4.5 times the 283,000 cubic yards estimated by EPA (shown in Table 3) in the OUFS.

Appendix D contains the EPA detailed waste volume calculations. Although twenty sample points (piles) were taken in each zone by EPA, the vast majority of the volume calculated by EPA for each area was not sampled and it is unertain how these volumes were estimated. A reverse calculation assuming the 283,000 cubic yards in an area of 891 acres yields an average depth of mine waste of only 2.36 inches, which from visual observation of the areas seems a gross underestimate. However, at 1,279,000 cubic yards in an area of 710 acres the average depth of mine waste would be 13.40 inches which seems more logical.

During the field work 54 out of the 160 EPA sampling point stakes were located, although an attempt to locate all stakes was not undertaken. All stakes located were on piles of bullrock, dump material, or overburden while none were observed on chat piles. As an additional exercise to compare individual pile volumes, these staked piles were measured in the field. Appendix E presents the comparison of volumetric data for these 54 piles. In essence the field measurements show an increase in pile volume of 370% over that estimated by EPA in Appendix D. This correlates fairly well with the 450% increase in the overall area volume of mine waste. The Appendix D data appears to have utilized standard pile cones with dimensions of 9 feet high and 31 feet in diameter or multiples of those dimensions. In reality, the piles are not nearly that standard or regular in shape.

In 1983 McCauley also estimated the size of a number of "chat" piles in the Galena area. His measurements were only of individual large piles and in reality did include some rock piles in addition to chat. If one assumes a standard cone shape for most and either a wedge or cube shape for the others, the range of volumes for 16 piles alone is from 293,000 to 392,000 cubic yards as shown in Table 4. Either of these values is greater than the EPA estimate for the whole area.

A further attempt to correlate volumes estimated in this study with McCauley's estimates yielded Table 5. This data indicates that, if anything, the estimates from this study may even be on the low side.

Table 2

Volume of Mine Waste

Area	Cubic Yards	Percent of Total
Zone l	161,156	12.6
		8.8
Zone 2	113,119	
Zone 3	90,652	7.1
Zone 4	56,318	4.4
Zone 5	306,821	24.0
Zone 6	81,703	6.4
Zone 7	377,791	29.5
Zone 8	91,495	7.2
Total	1,279,055 yd ³	
	34,534,485 ft ³	

Table 3

EPA Mine Waste Volume Summary

Zone	Volume Cubic Yards	Percent of Total
1	45,254	16.0
2	40,490	14.3
3	25,328	9.0
4	13,542	4.8
5	24,907	8.8
6	32,938	11.7
7	86,982	30.8
8	13,068	4.6
	282,509	100.0

Table 4
Estimates of Pile Volumes

McCauley Number	McCauley Measurements	Assumed Shape	Volume (yd³)
5	12.5' H x 400' dia.	Cone	19,400
8	25' H x 150' dia.	Cone	5,456
10	40' H x 300' dia.	Cone	34,920
12	300' W x 450' L x 20' H	Wedge-Cube	50,000-100,000
1.4	20' H x 100' día.	Cone	1,940
15	30' H x 180' dia.	Cone	9,428
18	150' W x 240' L x 30' H	Wedge-Cube	20,000-40,000
24	120' W x 300' L x 20' H	Wedge-Cube	13,333-26,667
25	75' H x 300' dia.	Cone	65 ,4 75
27	12.5' H x 250' dia.	Cone	7,578
28	125' W x 270' L x 12.5' H	Wedge-Cube	7,813-15,625
31	100' W x 200' L x 20' H	Wedge-Cube	7,408-14,815
34	25' H x 350' dia.	Cone	29,706
44	25' H x 220' dia.	Cone	11,737
45	12.5' H x 200' dia.	Cone	4,850
46	20' H x 150' dia.	Cone	4,365
	Total (range)		293,409-391,962

Table 5
Comparison of Volumes of Mine Waste

		Volume (yd ³)
McCauley Number	Andes Number	McCauley 1983	Andes 1988
4.4	1H-C7	11,737	3,468
45	1H-C8	4,850	6,291
31	2D-C5	7,408-14,815	7,113
34	3C-C5	29,706	13,227
25	7B-C2	65,475	75,972
10	6D-C1	34,920	33,880
18	52A-C1	20,000-40,000	25,937
12	5D-C1	50,000-100,000	39,115
1.4	6A-C2	1,940	3,323
5	8A-C3	19,400	18,969
	Totals	245,436-322,843	227,295

Although the OUFS did not attempt a breakdown of volumes or acreages by waste type, this study allowed such an evaluation. Table 6 presents a breakdown by type of surface mine waste observed. Although over 58% of the surface waste is chat, the waste rock estimate is still over 1.7 times the EPA estimate for the whole area.

Conclusions

Data and estimates of surface mine waste in the Galena Subsite generated by this study indicate that the waste volumes given by EPA in the OUFS have been grossly underestimated. Approximately 710 acres of mine waste area were mapped containing an estimated 1,279,000 cubic yards of surface mine waste. This represents an increase of around 450% more than presented in the OUFS. Such an additional amount would increase the operating time for any milling operation to around nine years with an attendant increase in operating and tailing disposal costs.

Correlation of the findings from this study with those from McCauley's 1983 survey indicated a general agreement in affected acreages and substantiated that estimated waste volumes may actually be on the low wide. McCauley's data further indicates the underestimation by EPA of the surface mine waste volume.

Based on this significant increase in surface mine waste volume, and thereby treatment costs, reevaluation of the remedial action alternatives by EPA would appear to be in order.

Table 6
Mine Waste Types

	Cubic				
	Acres	Yards			
Waste Rock	317.58	488,696	38		
Chat	311.79	735,639	58		
Overburden	2.46	19,840	2		
Stream Sediments	60.12	34,396	3		
Slag	.21	484	< 1		





45





11-M











AREAS DETERMINED BY PLANIMETER

Area lA	R1 C1 C2	.68					
Area lB	RI	.49					
Area 1C	C1	.77					
Area lD	R1 C1						
Area lE	R1	.75					
Area lF	Rl	. 49					
Area 1G	Rl	. 34					
Area lH							
Unmar	ked R1 R2 R3 R4 R5 R6 R7 R8 R9 R1 R1 R1	.30 .46 1.18 .35 2.57 1.91 10.34 5.50 .96 1 1.03 Pond 2 .40 3 4.71 4 9.21	minus .12 minus		C2 C3 C4 C5 C6 C7 C8 C9 C10 C11	1.40 1.16 3.60 .34 2.90 .20 4.30 3.90 1.59 9.23 5.37 4.42 3.53 .91 .27 .45	
Area 2A	C1 C2/R1 C3	Pond 1.76 Pond	.16		R2 Ponds	.88 (inside	area)
Area 2B	R1 R2 SS	5.33	.11	(insi	C 2 C 3 C 4		

Area 2C	C 1	5.53				
Area 2D	R1 R2	2.05 3.71		C l C 2	3.46 .96 Pond	. 23
	R3 R4 R5	.44 .44 9.02 Pond Pond Pond Pond	.14 .23 .10 .43	C3 C4 C5	4.32 5.37	• • •
Area 2DA	Cl	.91				
Area 2E	SSI	14.36				
Area 2F	Cl	1.10				
Area 3A	Cl	2.39				
Area 3B	Rl	2.94				
Area 3C	R1 R2	3.12 3.92		C1 C2	1.95 3.66 Pond	. 20
	R3	16.10		C3	8.70 Pond	.12
	R4	,66		C4	2.27 Pond	.37
	R5	16.07 minus Pond	C12	C 5	8.20	
	R6	7.40	• 10	C6	.98	
Ponds (inside	area)			C7 C8 C9 C10 C11 C12	2.20 6.69 5.18 .39 2.81	
Area 4	Rl	1.10	1 50	Cl	.12	
	R2	Pond 3.30	1.50	C 2	2.97	
	R3	Pond 3.28	. 22	C 3	2.26	
	R4	Pond 4.37	. 23	C 4	.27	
		Pond betwee R2 & F		C 5	. 37	
	SSI	1.33				

Area	4A	Cl	8.59				
Area	5D	C 1	4.85				
Area	5DA	Rl	2.69				
Area	52A	Rl Cl	.76 1.34				
Area	6A	R1 R2 R3 R4 R5 R6 R7 R8	.66 1.97 1.75 1.36 1.41 1.20 5.71 1.93 2.78		C1 C2 C3 C4	.14 2.06 .73 .19 Pond 1	.69
Area	6B	Cl	3.75				
Area	6C	Rl	.23				
Area	6 D	C 1	2.10				
Area	6 E	ssl	16.67				
Area	6EA	Rl	.15				
Area	7 A	R1 R2 R3 R4 R5 R6 R7 R8	.75 2.63 13.85 2.84 4.84 .97 2.03		C1 C2 C3 C4 C5	1.81 7.19 .56 1.22 2.78 3.01 .68	
		R9	5.34				
Po	ond (inside	area)		1.33			
Area	a 7B	R1 R2 R3 R4 R5 R6	4.90 1.18 .88 3.37 24.00 7.21		C1 C2 C3 C4 C5	3.48 3.14 7.39 2.68 1.70	
Po	ond (inside	SS1 area)	3.15	1.83			
	a 7C	Cl	15.71				

Area 8A	R1 R2 R3 R4 R5	.78 .40 .53 .20		C1 C2 C3 C4 C5 C6	.33 1.25 5.88 2.48 .01 3.68
	Sl	.13		OB1 OB2	1.85
Ponds	(inside area)		. 25		
Area 8B	Rl	15.68 Pond	.48	Cl	7.03
	R2 R3	1.68 3.18 Pond	. 49	C2 C3	3.61 .31

Ponds (inside area)



VOLUME CALCULATIONS

Zone	•		Height	Volume
Designat	ion	Acres	(ft)	(yd ³)
18	R1	.49	1.0	790
1C	Cl	.77	5.0	6,210
l D	Cl	1.34	U . 5	1,081
• -	R1	1.60	0.5	1,290
Subtotal		2.94		2,371
1 E	Rl	.75	0.5	605
lF	Rl	. 49	0.5	395
1 G	Rl	. 34	0.5	274
1 H	Cl	1.40	3.0	6,775
	C 2	1.16	1.0	1,871
	C 3	3.60	2.0	11,614
	C 4	.34	3.0	1,645
	C5	2.90	0.5	2,339
	C6	.20	3.0	968
	C7	4.30	0.5	3,468
	C8	3.90	1.0	6,291
	C9	1.59	1.0	2,565
	C10	9.23	1.5	22,332
	C11	5.37	1.0	8,662
	C12	4.42	0.5	3,565
	C 1 3	3.53	0.5	2,847
	C14	.91	0.5	734
	C15	. 27	1.0	436
	C16	. 45	5.0	3,629
	Rl	5.95	1.0	9,597
	R2	.30	2.0	968
	R3	.46	5.0	3,710
	R4	1.18	0.5	952
	R 5	. 35	0.5	282
	R6	2.57	0.5	2,073
	R7	1.91	. 25	770
	R8	10.14	0.5	8,178
	R9	5.50	1.0	8,872
	R10	.96	2.0	3,097
	Rll	. 91	2.0	2,936
	R12	. 40	2.0	1,290
	R13	4.71	0.5	3,799
	R14	8.94	. 25	3,605
	SSI	3.18	. 25	1,282
	SS2	7.21	. 25	2,907
	Pond	.12	_	124 050
Subtota	1	98.36		134,059

Zone	,	D	Height	Volume
Designat	ion	Acres	(ft)	(yd)
2C	C 1	5.53	1.0	8,920
2D	C1 C2 C3 C4 C5 R1 R2 R3 R4 R5 S1 Ponds	3.46 .96 4.32 5.37 4.41 2.05 3.71 .44 .44 8.12 .08 1.13 34.49	1.0 1.0 1.0 .25 1.0 0.5 1.0 0.5 0.5	5,581 1,548 6,968 2,165 7,113 1,653 5,984 355 355 19,646 65
Subtotal		34.49		51,455
2 D A	C1	.91	. 25	367
2E	ssl	14.36	. 25	5,791
2F	C 1	1.10	1.0	1,774
lA Subtotal	C1 C2 R1	.68 1.18 <u>3.94</u> 5.80	4.0 3.0 1.0	4,387 5,710 6,355 16,452
2A	C1 C2/R1 C3 R2 Ponds	5.83 1.51 4.29 .88 .41	.25 1.0 0.5 1.0	2,351 2,436 3,460 1,419
Subtotal		12.92		9,666
2B	C1 C2 C3 C4 R1 R2 SS1	1.17 1.01 .90 2.51 15.87 5.33 1.75	.25 1.0 1.0 .25 1.0 0.5	472 1,629 1,452 1,012 25,598 4,299 706
Subtotal		28.65		
3A	C1	2.39	0.5	1,927
3B	Rl	2.94	0.5	2,371

Zone			Height	Volume
Designation		Acres	(ft)	(yd ³)
3C	C1 C2 C3 C4 C5 C6 C7 C8 C9 C10 C11 C12 R1 R2 R3 R4 R5 R6 Ponds	1.95 3.46 8.58 1.90 8.20 .98 2.20 6.69 5.18 .39 2.81 .35 3.12 3.32 16.10 .66 15.62 7.40 .79	.25 0.5 1.5 0.5 1.0 0.5 0.5 1.0 .25 0.5 0.5 1.0 1.0 1.0 1.0	786 2,790 20,759 1,532 13,227 790 1,774 10,791 2,089 315 2,266 282 5,032 5,355 12,985 1,597 12,598 5,968
Subtotal		89.70		86,354
4 Subtotal	C1 C2 C3 C4 C5 R1 R2 R3 R4 SS1 Ponds	.12 2.97 2.26 .27 .37 1.10 3.08 2.68 4.37 1.33 2.11 20.66	3.0 0.5 1.0 2.0 10.0 8.0 1.0 2.0 1.0 0.5	581 2,395 3,645 871 5,968 14,194 4,968 8,646 7,049 1,073
4A	Cl	8.59	0.5	6,928
5B Subtotal	Cl Rl	.57 2.02 2.59	2.0	1,839 3,258 5,097
5C	Rl	2.65	0.5	2,137
5E	Rl	1.08	1.0	1,742
5EA	Rl	~2.10	1.0	3,387
5AB Subtotal	C1 R1 R2 R3 R4	.32 .77 1.64 2.19 5.77 10.69	1.0 5.0 0.5 5.0 .25	516 6,210 1,323 17,662 2,327 28,038

Zone			Height	Volume
Designat	ion	Acres	(ft)	(yd ³)
5A	Cl	2.31	. 25	932
	C 2	3.51	0.5	2,831
	C 3	.57	0.5	460
	C 4	1.29	1.0	2,081
	C 5	7.03	0.5	5,670
	C6	9.74	. 25	3,928
	C7	13.27	1.0	21,405
	C8	3.53	0.5 5.0	2,847 20,566
	C9	2.55	.25	1,165
	C10	2.89 3.78	1.0	6,097
	Cll	1.06	5.0	8,549
	C12	2.85	0.5	2,299
	C13 C14	2.25	2.0	7,259
	C14	3.36	2.0	10,839
	C16	. 27	5.0	2,178
	C17	2.00	0.5	1,613
	C18	2.69	2.0	8,678
	C19	7.86	. 25	3,170
5 A	Rl	1.43	0.5	1,153
J.,	R2	1.65	. 25	665
	R3	2.16	2.0	6,968
	R4	1.56	4.0	10,065
	R 5	1.10	1.0	1,774
	R6	.85	3.0	4,113
	R7	1.90	0.5	1,532
	R8	2.30	4.0	14,840
	R10	.97	3.0	4,694
	Rll	.53	5.0	4,274
	R12	1.80	5.0	14,517
	R13	1.28	1.5	3,097
	R14	2.10	1.0	3,387
	R15	2.00	0.5	1,613 738
	R16	1.83	. 25	1,008
	R17	2.50	.25 .25	407
	R18 R19	1.01 1.36	. 25	548
	SSI	3.35	0.5	2,702
	SS2	3.20	. 25	1,290
	Ponds	6.35	-	· -
Subtotal		114.04		191,952
D	C 1	4.85	5.0	39,115
5DA	Rl	2.69	1.0	4,339
52 A	Cl Rl	1.34 .76	12.0 1.0	25,937 1,226
Subtotal		2.10	- • · ·	27,163

Zone		Naras	Height (ft)	Volume (yd ³)
Designat	1011	Acres	(11)	(ya)
6.A	Rl	.66	1.0	1,065
	R2	1.97	. 25	794
	R3	1.75	1.0	2,823
	R4	1.36	0.5	1,097
	R5	1.41	1.0	2,274
	R6	1.20	1.0	1,936
	R7	5.71	. 25	2,303
	R8	1.93	0.5	1,557
	R9	2.78	2.0	8,968
	Cl	. 14	1.0	226
	C 2	2.06	1.0	3,323
	C 3	.73	0.5	589
	C 4	.19	0.5	153
	SSl	1.00	. 25	403
	Pond	1.69	-	-
Subtotal		24.58		27,511
6B	C 1	3.75	1.0	6,049
6C	Rl	.23	. 25	93
6 D	Cl	2.10	30	33,880
			(cone)	
			, ,	
6 E	SSl	16.67	.50	13,444
6EA	Rl	.15	3.0	726
7A	Cl	1.81	5.0	14,598
	C2	7.19	4.0	46,390
	C 3	.56	1.0	903
	C 4	1.22	1.0	1,963
	C 5	2.78	1.0	4,484
	R1	.75	. 25	302
	R 2	2.63	. 25	1,061
	R3	13.85	1.0	22,340
	R4	2.84	1.0	4,581
	R5	4.84	1.5	11,710
	R6	.97	4.0	6,258
	R7	2.03	2.0	6,549
	R8	.89	0.5	718
	R9	5.34	1.0	8,613
	SSI	3.01	. 25	1,214
	SS2	.68	0.5	548
C. h 1	Pond	$\frac{1.33}{52.72}$	-	$\frac{-}{132,237}$
Subtotal	•	52.72		132,23/

2one			Height	Volume
Designation		Acres	(ft)	(yd ³)
7B	C1 C2 C3	3.48 3.14 7.39	6.0 15.0 3.0	33,679 75,972 35,760
	C4 C5 R1 R2 R3 R4	2.68 1.70 4.90 1.18 .88 3.37	4.0 3.0 .25 0.5 0.5	17,291 8,226 1,976 952 710 5,436
Subtotal	R5 R6 SS1 Pond	24.00 7.21 3.15 1.83 64.91	1.0 1.0 0.5	38,712 11,630 2,540 232,884
7C	Cl	15.71	0.5	12,670
5AA Subtotal	C1 R1 R2 SS1 Pond	.21 1.23 .43 1.23 .09 3.19	2.0 1.0 1.0 .25	677 1,984 694 496 ——————————————————————————————
8A Subtotal	C1 C2 C3 C4 C5 C6 R1 R2 R3 R4 R5 S1 OB1 OB2 Ponds	.33 1.25 5.88 2.48 .01 3.68 .78 .40 .53 .20 .49 .13 1.85 .61 .69 19.31	3.0 1.0 2.0 1.0 3.0 1.0 2.0 0.5 0.5 4.0 2.0 2.0 5.0	1,597 2,016 18,969 4,000 48 5,936 2,516 323 427 1,290 1,581 419 14,920 4,920 - 58,962
Subtotal 8B Subtotal	C1 C2 C3 R1 R2 R3 Ponds	7.03 3.61 .31 15.20 1.68 2.69 .97 31.49	1.0 0.5 5.0 0.5 0.5	11,339 2,911 2,500 12,259 1,355 2,169

APPENDIX D

HINE WASTE VOLUME ESTIMATES FOR CHEROKEE COUNTY KANSAS

SITE	SAMPLE	VOLUME	X TOTAL	Height	Dia.	L	٧	Partial	Volumes (c	u ft)
		(cu yde)	VOLUME	(It)	(It)	(1t)	(1t)	Cone		Fill
1	1	85	e. 2x	9	31			2283	•	
1	2	85	9. 2X	9	31			2283		
1	3	5411	12. 0%	36	125			146093		
1	4	676	1. 5X	18	63			18262		
1	5	85	e. 2x	9	31			2283		
1	6	85	e. 2x	9	31			2283		
1	7	5411	12. G X	36	125			146093		
1	8	85	e. 2x	9	31			2283		
1	9	676	1.5x	18	63			18262		
1	10	85	e. 2%	9	31			2283		
1	11	85	0. 2%	9	31			2283		
1	12	85	0. 2X	9	31			2283		
1	13	85	e. 2x	9	31			2283		
1	14	65	6. 2X	9	31			2283		
1	15	85	0. 2%	9	31			2283		
1	16	85	e. 2x	9	31			2283		
1	17	85	6. 2X	9	31			2283		
1	18	676	1.5%	18	63			18262		
1	19	2283	5. e x	27	94			61633		
1	20	5411	12. ex	36	125			146093		
1		568	1.3%	15	63			15340		
1		3788	8. 4X	8	31	x50		102265		
1		34 09	7.5%	10	188			92039		
1		568	1.3%	15		x10		15340		
1		15278	33. 8%	15		1100	50		412500	

TOTAL 45254 CU YDS

HINE WASTE VOLUME ESTIMATES FOR CHEROKEE COUNTY KANSAS

Estimated from approximate height, length, width and dismeter of waste dumps observed in the field and on serial photos

SITE	SAMPLE	VOLUME	X TOTAL	Height	Dia.	L	٧	Partial	Volumes	(cu ft)
		(cu yds)	VOLUME	(1t)	(1t)	(1t)	(1t)	Cone	Wedge	F111
2	1	85	0. 2x	9	31			2283	_	
2	2	85	9. 2X	9	31			2283		
2	2	85	0. 2X	9	31			2283		
2	4	85	e. 2x	9	31			2283		
2	5	85	0. 2X	9	31			2283		
2	6 7	85	e. 2x	9	31			2283		
2	7	85	e. 2x	9	31			2283		
2 2	8	85	0. 2X	9	31			2283		
2	9	85	e. 2x	9	31			2283		
2	10	85	e. 2x	9	31			2283		
2	11	85	e. 2x	9 9 9	31			2283		
2	12	85	e. 2x	9	31			2283		
2	13	676	1.7%	18	63			18262		
2	14	676	1.7%	18	63			18262		
2	15	676	1.7%	18	63			18262		
2	16	676	1.7%	18	63			18262		
2	17	676	1.7%	18	63			18262		
2	18	676	1.7%	18	63			18262		
2	19	85	0. 2X	9	31			2283		
2	20	85	0. 2%	9	31			2283		
2		1023	2.5%	4	94					2761
2		1818	4.5%	4	125					4908
2		18519	45.7%	1		1000	500			50000·
2		13889	34.3%	1		7 50	500			37500

TOTAL 40490 CU YDS

HINE WASTE VOLUME ESTIMATES FOR CHEROKEE COUNTY KANSAS

					84.5	L	¥	-Pertiel-	-Volumes-	(cu it)-
SITE S	AHPLE V	OLUNE	% TOTAL /		Dia.	(1t)	(ft)	Cone	Wedge	Fill
	(c	u yds)	AOLUME	(ft)	(1t)	(IL)	(20)	16107		
3	1	597	2. 4%	7	94			8181		
3	2	303	1.2%	8	63			6136		
3	3	227	6. 9%	6	63			6136		
3	4	227	0. 9%	6	63			6136		
3	Š	227	0. 9%	6	63			2283		
3	6	85	e. 3¥	9	31			2283		
3	7	85	e. 3x	9	31			2283		
		85	e. 3%	9	31			2283		
3 3	8 9	85	e. 3%		31			2283		
	10	85	e. 3x	_	31			2283		
3		85	e. 3%	_	31			2283		
3	11	85	0. 3%	_	31			2283		
3	12	85	0.3%	_	31					
3	13	85	e. 3X	_	31			2283		
3	14		e. 3x	_	31			2283		
3	15	85	1.3%	_	63			92 04		
3	16	341		_	31			2283		
3	17	85	e. 3X	_	31			2283		
3	18	85	e. 3x		31			2283		
3	19	85	0.31	_	31			2283		
3	20	85			31	200	a 3	00		600000
3		22222	87.79	1		200	•	· - -		

TOTAL 25328 CU YDS

HINE WASTE VOLUME ESTIMATES FOR CHEROKEE COUNTY KANSAS

SITE	SAMPLE	VOLUME	X TOTAL	Height	Dia.	L	¥	-Partial-	-Volumes-	(cu ft)-
	((cu yds)	AOLUME	(ft)	(1t)	(1t)	(ft)	Cone	Wedge	F111
4	1	85	0. 6X	9	31			2283	-	
4	2	85	e. 6x	9	31			2283		
4	3	85	9. 6X	9	31			2283		
4	4	85	8. 6X	9	31			2283		
4	5	85	6. 6X	9	31			2283		
4	6	85	0. 6X	9	31			2283		
4	7	85	e. 6x	9	31			2283		
4	8	85	0. 6X	9	31			2283		
4	9	85	0. 6X	9	31			2283		
4	10	85	0. 6X	9	31			2283		
4	11	85	e. 6x	9	31			2283		
4	12	676	5. 9%	18	63			18262		
4	13	85	6. 6X	9	31			2283		
4	14	85	0. 6X	9	31		•	2283		
4	15	676	5. e x	18	63			18262		
4	16	65	e. 6x	9	31			2283		
4	17	85	e. 6x	9	31			2283		
4	18	85	e. 6x	9	31			2283		
4	19	85	e. 6x	9	31			2283		
4	20	42	e. 3x	9	31 /	/2		1141		
4	21	42	e. 3%	9	31 /			1141		
4		3382	25. 0%	18	63 :			913 98		
4		7285	53. 8%	12	31	1250	25	92 94	187 500	

TOTAL 13542 CU YDS

HINE WASTE VOLUME ESTIMATES FOR CHEROKEE COUNTY KANSAS

	of ve	ste dumps	observed :	IN the II.	710 Bild 50		•				4.
a.e.		E VOLUME	% TOTAL	Height	Dia.	L	_	W (ft)	-Partial	-Volumes- Wedge	fill
2115	SARF	(cu yds)		(ft)	(1t)	(1t)	(10)	2283		
_	. 1			9	31				2283		
5	,	_		_	31				18262		
3	,	2 85 3 676		18	63				2283		
3		8		_	31				2283		
		5 8			31				2283		
		_		9	31				2283		
	•	6 8: 7 8:			31				2283		
	-				31				18262		
	<u> </u>	8 8: 9 67:			63				18262		
	_	67			63				18262		
	3	1 67		<u> </u>	63				2283		
			5 0.3	9 9	31				2283		
			5 0.3	x 9	31	•			2283		
			5 0.3	x 9	31				2283		
			is e. 3	<u> </u>	31				2283		
			5 0.3	x 9	31				2283		
			5 0.3	1 9	31				2283		
			5 6.3	x 9	31				61633		
	5	19 22		12 27	94				18262		
			76 2.7	'Y 18			188	6			!
	5 5	45		18			100		57968		
	5	21		5% 9		x25			182617		
	5	67			63	x10		25			125000
	5	46					500		-		

TOTAL 24987 CU YDS

HINE WASTE VOLUME ESTIMATES FOR CHEROKEE COUNTY KANSAS

	OI AFR	e dampe		=							
					04.5	L		٧	-Partial	Volumes-	cu It)-
SITE	SAMPLE	VOLUME	% TOTAL	Height	Dia.	(1t)		(1t)	Cone	Wedge	Fill
		(cu yds)	VOLUME	(ft)	(1 t)	(10)	,		3297		
6	1	119	0.4 %	10	35				2929		
6	2	75	e. 2%	9	30				4787		
6	2 3	177	e. 5%		40				3351		
6	4	124	e. 4x		40				13090		
6	5	485	1.5%	20	50				9817	140625	
	6	5572	16.9%	15	50		375		- 56549	• • • • • • • • • • • • • • • • • • • •	
6	7	2094	6. 4%	_	129				2283		
6		85	e. 3x	_	31						
6	8	85	0. 3X	_	31				2283		
6			0. 3X	_	31				2283		
6		85	e. 6x		40				5027		
6	11	186	0.1%	_	25				1169		
6		43		·	35				4811		
6		178	e. 5x		35				4811		
6	14	178			35				4811		
6	15	178		_	20				838		
6	16	31			35				4811		
6		178			30		100	10			30000
6	18	1111			186	13			164355		
6		6007							164355		
ē			18.5		188				164355		
	21		18.5		188				34241		
	,	1264		x 9		x15			65450		
	5	2424		x 14	50	x 7			55.55		
,	3		-								

TOTAL 32938 CU YDS

HINE WASTE VOLUME ESTIMATES FOR CHEROKEE COUNTY KANSAS

					_		₩	- F	ertial	Volumes-(cu ft)-
SITE	SAMPLE	VOLUME	% TOTAL	Height	Dia.	L			Cone	Vedge	F111
32	J	(cu yde)	VOLUME	(It)	(1t)	(1t	., (10	•	61633		
7	1	2283	2.6X	27	94				2283		
7	2	85	0. 1X	9	31				2283		
7	2	85	0.1%	9	31				2283		
7	. J	85	0.1%	9	31				18262		
	5	676	0. 8X		63				2283		
7		85	0.1%		31				2283		
7	6 7	85	0.1%	_	31				2283		
7		85	0. 1X	_	31				2283		
7	8	85 85	0. 1X	_	31						
7	9		0. 1X	_	31				2283		
7	10	85	0. 1X	_	31				2283		
7	11	85	0. 1X	_	31				2283		
7	12	85	0. 1X	9	31				2283		
7	13	85	0. 17		31				2283		
7			0. 17	_	31				2283		
7		_		_	31				2283		
7	16			_	31				2283		
7	17				94				61633		
7	18				63				18262		
7	19	676	O. A:		31				2283		
7		65	0. 13			×75			171293		
7	,	6341							273925		
7	,	10145	11.7	¥ 18		x15	100 x10		32070	175000	
-		7669			35		4000	750			1500000
		55556		x 1			1000	, 50			

TOTAL 86982 CU YDS

HIME WASTE VOLUME ESTIMATES FOR CHEROKEE COUNTY KANSAS

	01 448	CG GG-P-								
SITE	SAMPLE	VOLUME (cu yds)	X TOTAL VOLUNE	Height (ft)	Dia.	L (ft)	4 (1t)	-Pertial Cone 18262	-Volumes- Vedge	fill
_	_	676	5. 2%	18	63					
8	1		5. 2X	18	63			18262		
8	2	676			50			93 50		
8	3	346	2.6%	14				9350		
8	4	346	2. 6X	14	50			9350		
8		346	2. 6X	14	50			9350		
a		346	2. 6X	14	50			9350		
		346	2. 6X		50					
8			2.6%		50			9350		
8		346	2. 6X		50			93 50		
8		346		_	31			2283		
8	10	85	0. 6X	_	31			2283		
8	11	85	e. 6x	_				2283		
8		85	e. 6x		31			2283		
8			e. 6x		31			2283		
ě			0. 6X	9	31					
					31			2283	10750	
٤				· .	25	154		1636	18759	
•				·	63			18262		
	17				63			18262		
	3 18	676				150	.	9350	53571	•
	3 19	2336			50	154		3297		
	8 20		0. 91		35			22827		
	5 5	845		y 9		x10		91366		
	8	3382			63	x5		31300		

TOTAL 13068 CU YDS



COMPARISON OF PILE VOLUMES

	CH ₂ M Hill	G. Andes	
Location	Volume	Volume	
Number	(ft ³)	(ft ³)	
Number	<u> </u>	(10)	
2 2	2 202	11.070	
2-3 3-1	2,283 16,107	14,079 24,960	
3-2	8,181	6,739	
3-3	6,136	7,372	
3-5	6,136	148,078	
3-6	2,283	5,158	
3-7	2,283	40,562	
3-8	2,283	50,965	
3-11	2,283	103,915	
3-12 3-13	2,283 2,283	70,200 28,431	
3-16	9,204	97,998	
3-17	2,283	36,055	
3-20	2,283	11,271	
4-10	2,283	14,759	
4-11	2,283	11,310	
4-12	18,262	99,688	
4-13	2,283	60,937	
4-14	2,283	7,582	
8-3 8-6	9,350 9,350	11,243 9,370	
8-7	9,350	20,631	
8-8	9,350	14,438	
8-9	9,350	24,375	
8-10	2,283	4,424	
8-15	2,283	13,120	
8-16	20,386	277,300	
8-18	18,262	61,893 450	
1 – 4 1 – 7	18,262 146,093	180,000	
1-16	2,283	7,023	
1-17	2,283	17,230	
2-1	2,283	26,957	
2-2	2,283	2,986	
2-4	2,283	8,485	
2-6	2,283	9,370	
2-7	2,283	13,130	
2-8 2-9	2,283 2,283	5,852 55,814	
2-12	2,283	11,846	
2-15	18,262	16,433	
2-19	2,283	8,226	
1-18	18,262	10,618	
6-4	3,351	17,342	
6-1	3,207	2,633	

		CH ₂ M Hill	G. Andes	
Location		Volume	Volume	
Number		(ft ³)	(ft ³)	
6-5		13,090	1,877	
6-6		9,817	7,108	
6-12		1,169	3,775	
6-13		4,811	9,984	
5-10		18,262	15,000	
5-6		2,283	609	
7-8		2,283	7,256	
7-17		2,283	8,200	
1-2		2,283	26,364	
	TOTAL	472,500	1,751,421	371% Increase

54 out of 160 points Andes + 45 Andes - 9